


HIGH-SECURITY MULLION READER

RFID CARDS, NFC & BLUETOOTH®



13.56 MHz



BLUETOOTH®



TTL
RS485



Water
resistant
EQ IP65



Vandal-proof
IK10



4 COLOR LOGO

- Add your logo
- 2 configurable multicolor LEDs
- Casing colors
- Skin effect customization

Compatible with all access control systems, Architect® One Blue is an extremely compact reader for RFID cards and Bluetooth® & NFC smartphones for mounting on narrow surfaces.

SLEEK DESIGN FOR EASY INSTALLATION

The mullion reader is designed to be installed in spaces requiring a small footprint: door frames, narrow electrical junction boxes, sliding doors, fast access control corridors, elevators.

Its optimized design ensures perfect integration, whatever the installation environment and without additional spacers (even on metal). The pluggable cable and the mounting base make it very easy to install.

WELCOME TO HIGH SECURITY

The reader allows the secure identification of users thanks to its multiple identification technologies.

Bluetooth® and NFC

The smartphone becomes your access key and erases all the constraints of traditional access control.

STid offers 5 identification modes - Prox, long distance or hands-free - to make your access control both secure and instinctive!

RFID MIFARE® DESFire® EV2 & EV3

The reader supports the latest contactless technologies with the newest data security devices:

- **Secure Messaging EV2:** transaction security that protects against interleaving and replay attacks.
- **Proximity Check:** protection against relay attacks.

It integrates recognized and approved security mechanisms such as public algorithms and an EAL5+ certified crypto processor to protect your data stored in the reader.

ULTIMATE SELF-PROTECTION

The patented motion sensor pull detection system protects sensitive data by allowing authentication keys to be erased.

Unlike existing solutions within this market, the reliability of the accelerometer avoids potential system bypass.

OPEN TECHNOLOGIES FOR EASY INTEGRATION

The reader is compatible with all access control systems and accepts multiple interfaces and protocols (Wiegand, Clock&Data, SSCP® and OSDP™).

OUR SECURITY OFFERINGS

- **Easyline:** readers and cards pre-configured and programmed, ready to use.
- **Expert line:** you program your readers and cards in perfect autonomy with the intuitive configuration tools.
- **Individual line:** we offer a wide range of Premium services to configure and customize your readers and credentials according to your needs.

Find out more ▶



SPECIFICATIONS

| | | | | | | | | | | | | | | | | | | | | | |
|---|--|---|----------------------|------------------------------|----------------------|--|----------------------|--------------------------------|-----------------------|---|-----------------------|--|-----------------------|---|-----------------------|---|-----------------------|---|-----------------------|---|-----------------------|
| Operating frequency / Standards | 13.56 MHz: ISO14443 types A & B, ISO18092 Bluetooth® | | | | | | | | | | | | | | | | | | | | |
| Chip Compatibilities | MIFARE® Ultralight® & Ultralight® C, MIFARE® Classic & Classic EV1, MIFARE Plus® (S/X) & Plus® EV1, MIFARE® DESFire® 256, EV1, EV2 & EV3, CPS3, NFC (HCE), PicoPass® (CSN only), iCLASS™ (CSN only*) STid Mobile ID® (NFC and Bluetooth® virtual card), Orange Pack ID | | | | | | | | | | | | | | | | | | | | |
| Functions | Read only CSN, pre-configured (Easyline - PC2) and secure (file, sector) / Protocol-driven (read-write) | | | | | | | | | | | | | | | | | | | | |
| Communication interfaces & protocols | TTL Clock&Data (ISO2) or Wiegand output (encrypted communication option - S31) / RS485 output (encrypted option - S33) with SSCP® v1 & v2 secure communication protocols; OSDPT™ v1 (plain) and v2 (SCP secure) | | | | | | | | | | | | | | | | | | | | |
| Decoder compatibility | Compatible with EasySecure interface (encrypted communication) | | | | | | | | | | | | | | | | | | | | |
| Reading distances** | Up to 6 cm / 2.36" with a MIFARE® DESFire® EV2 card Up to 20 m / 65.6 ft with a Bluetooth® smartphone (adjustable distances on each reader) | | | | | | | | | | | | | | | | | | | | |
| Data protection | Yes - Software protection and EAL5+ crypto processor for secure data storage | | | | | | | | | | | | | | | | | | | | |
| Light indicator | 2 RGB LEDs - 360 colors ▲ ▲ ▲ Configurable by card (classic or virtual with STid Settings application), software or controlled by external command (0V) depending on interface | | | | | | | | | | | | | | | | | | | | |
| Audio indicator | Integrated buzzer with adjustable intensity Configurable by card (classic or virtual with STid Settings application), software or controlled by external command (0V) depending on interface | | | | | | | | | | | | | | | | | | | | |
| Consumption / Power supply | 150 mA/12 VDC Max - 9 VDC to 15 VDC | | | | | | | | | | | | | | | | | | | | |
| Connectors | Cable with plug connector 3 m / 9.8 ft | | | | | | | | | | | | | | | | | | | | |
| Material | ABS-PC UL-V0 (black) / ASA-PC-UL-V0 UV (white) | | | | | | | | | | | | | | | | | | | | |
| Dimensions (h x w x d) | 111.5 x 42.2 x 22 mm / 4.39" x 1.66" x 0.86" (general tolerance according to standard ISO NFT 58-000) | | | | | | | | | | | | | | | | | | | | |
| Operating temperatures | - 30°C to + 70°C / - 22°F to + 158°F | | | | | | | | | | | | | | | | | | | | |
| Tamper switch | Accelerometer-based tamper detection system with key deletion option (patented solution) and/or message to the controller | | | | | | | | | | | | | | | | | | | | |
| Protection / Resistance | UL294 Outdoor and Indoor rated / IP65 level - Tropicalized electronics according to standard CEI NF EN 61086 - Weather, water and dust resistant / Humidity: 0 - 95% / IK10 certified vandal-proof reinforced structure | | | | | | | | | | | | | | | | | | | | |
| Mounting | Wall-mounted, on door jambs and on narrow electrical pots (32 mm / 1.26" x 2 holes) Mounting on any type of support including metal without spacer | | | | | | | | | | | | | | | | | | | | |
| Certifications | CE (Europe), FCC (USA), UL294 (USA), IC (Canada), UKCA (UK) and UL | | | | | | | | | | | | | | | | | | | | |
| Part numbers y: casing color (1: black - 2: white) | <table border="0"> <tr> <td>Pre-configured read-only Easyline - Wiegand</td> <td>ARC1S-R31-B/PC2-3x/1</td> </tr> <tr> <td>Secure read-only - TTL</td> <td>ARC1S-R31-B/BT1-xx/y</td> </tr> <tr> <td>Secure read-only / Secure Plus - TTL</td> <td>ARC1S-S31-B/BT1-xx/y</td> </tr> <tr> <td>Secure read-only - RS485</td> <td>ARC1S-R33-B/BT1-7AB/y</td> </tr> <tr> <td>Secure read-only / EasySecure interface - RS485</td> <td>ARC1S-R33-B/BT1-7AA/y</td> </tr> <tr> <td>Secure read-only / Secure Plus - RS485</td> <td>ARC1S-S33-B/BT1-7AB/y</td> </tr> <tr> <td>Secure read-only / Secure Plus / EasySecure interface - RS485</td> <td>ARC1S-S33-B/BT1-7AA/y</td> </tr> <tr> <td>Controlled by SSCP® v1 protocol - RS485</td> <td>ARCIS-W33-B/BT1-7AA/y</td> </tr> <tr> <td>Controlled by SSCP® v2 protocol - RS485</td> <td>ARCIS-W33-B/BT1-7AD/y</td> </tr> <tr> <td>Controlled by OSDPT™ v1 & v2 protocol - RS485</td> <td>ARCIS-W33-B/BT1-7OS/y</td> </tr> </table> | Pre-configured read-only Easyline - Wiegand | ARC1S-R31-B/PC2-3x/1 | Secure read-only - TTL | ARC1S-R31-B/BT1-xx/y | Secure read-only / Secure Plus - TTL | ARC1S-S31-B/BT1-xx/y | Secure read-only - RS485 | ARC1S-R33-B/BT1-7AB/y | Secure read-only / EasySecure interface - RS485 | ARC1S-R33-B/BT1-7AA/y | Secure read-only / Secure Plus - RS485 | ARC1S-S33-B/BT1-7AB/y | Secure read-only / Secure Plus / EasySecure interface - RS485 | ARC1S-S33-B/BT1-7AA/y | Controlled by SSCP® v1 protocol - RS485 | ARCIS-W33-B/BT1-7AA/y | Controlled by SSCP® v2 protocol - RS485 | ARCIS-W33-B/BT1-7AD/y | Controlled by OSDPT™ v1 & v2 protocol - RS485 | ARCIS-W33-B/BT1-7OS/y |
| Pre-configured read-only Easyline - Wiegand | ARC1S-R31-B/PC2-3x/1 | | | | | | | | | | | | | | | | | | | | |
| Secure read-only - TTL | ARC1S-R31-B/BT1-xx/y | | | | | | | | | | | | | | | | | | | | |
| Secure read-only / Secure Plus - TTL | ARC1S-S31-B/BT1-xx/y | | | | | | | | | | | | | | | | | | | | |
| Secure read-only - RS485 | ARC1S-R33-B/BT1-7AB/y | | | | | | | | | | | | | | | | | | | | |
| Secure read-only / EasySecure interface - RS485 | ARC1S-R33-B/BT1-7AA/y | | | | | | | | | | | | | | | | | | | | |
| Secure read-only / Secure Plus - RS485 | ARC1S-S33-B/BT1-7AB/y | | | | | | | | | | | | | | | | | | | | |
| Secure read-only / Secure Plus / EasySecure interface - RS485 | ARC1S-S33-B/BT1-7AA/y | | | | | | | | | | | | | | | | | | | | |
| Controlled by SSCP® v1 protocol - RS485 | ARCIS-W33-B/BT1-7AA/y | | | | | | | | | | | | | | | | | | | | |
| Controlled by SSCP® v2 protocol - RS485 | ARCIS-W33-B/BT1-7AD/y | | | | | | | | | | | | | | | | | | | | |
| Controlled by OSDPT™ v1 & v2 protocol - RS485 | ARCIS-W33-B/BT1-7OS/y | | | | | | | | | | | | | | | | | | | | |

CREDENTIALS AND USER-FRIENDLY MANAGEMENT TOOLS



13.56 MHz or dual frequency
ISO cards & key holders



NFC and Bluetooth®
Smartphones / connected watches
with STid Mobile ID® application



SECard
SECard configuration kit and
SSCP® v1 & v2 and OSDPT™ v1 & v2 protocols



STid Mobile ID®
Online Portal
Web platform for remote management
of your virtual cards

* Our readers only read the / UID PICO1444-3B serial number of the iCLASS™ chip. They do not read the cryptographic protections iCLASS™ nor the / UID PICO 15693 serial number of HID Global.

**Caution: information about the distance of communication: measured from the center of the antenna, depending on the type of credential, size of the credential, operating environment of the reader, temperatures, power supply voltage and reading functions (secure reading). External interference may reduce reading distances.

Legal: STid, STid Mobile ID® Architect® and SSCP® are registered trademarks of STid SAS. All trademarks mentioned in this document belong to their respective owners. All rights reserved - This document is the property of STid. STid reserves the right to make changes to this document and to cease marketing its products and services at any time and without notice. Photos are not contractually binding.

Headquarters / EMEA

13850 Grésasse, France
Tel.: +33 (0)4 42 12 60 60

PARIS-IDF

92290 Châtenay-Malabry, France
Tel.: +33 (0)1 43 50 11 43

STid UK Ltd.

Gallows Hill, Warwick CV34 6UW, UK
Tel.: +44 (0) 192 621 7884

NORTH AMERICA

Irving, Texas 75063-2670, USA
Tel.: +1 877 894 9135

LATINO AMERICA

San Rafael 06470 CDMX, México
Tel.: +52 (55) 5256 4706

MIDDLE EAST

Dubai Digital Park, DSO, UAE
Tel.: +971 521 863 656