

## CD42 Indoor Dome Camera

# Reliable 5MP Coverage for Extensive Visibility in Indoor Spaces



## Overview

The CD42 dome camera – the backbone of enterprise fleet deployments – provides reliable 5MP coverage in a variety of indoor environments. With a 1 / 2.8" progressive CMOS image sensor and 15 meters / 49 feet of IR range, the CD42 ensures consistent image quality in any lighting condition. The CD42 includes an onboard CV25S Ambarella processor to support advanced analytics like AI-powered search, [Occupancy Trends](#), line crossing, loitering, and Person of Interest (POI) alerts. The CD42 excels at covering indoor spaces like hallways and retail floors, providing extensive coverage with detailed people analytics without sacrificing image quality.

The CD42's sleek design and IK08 impact rating enable organizations to deploy a durable, tamper-resistant camera while also keeping aesthetics top-of-mind. Installation is simple and intuitive, and setup is easy to track with an LED status indicator. The included mount plate additionally allows the camera to be mounted to a wall or ceiling without any additional hardware.

## Key features

### Excellent image quality

- 1 / 2.8" progressive CMOS image sensor
- 5MP resolution
- 15 meters / 49 feet of IR range for well-defined nighttime viewing

### Advanced analytics

- Onboard CV25S Ambarella processor enables people and vehicle analytics
- AI-powered search and AI-powered alerts
- Occupancy Trends for operational insights

### Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 365 days (256GB - 2TB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

### Easy installation

- Mounting plate and screw pack included
- LED light status indicator
- Digital mute switch to quickly enable or disable audio



## CD42

### Tech Specs

#### Camera features

|  |  |                             |   |
|--|--|-----------------------------|---|
| <b>Image Sensor</b>                          | 1 / 2.8" Progressive CMOS  | <b>Shutter Speed</b>        | 1 / 30 sec. to 1 / 10,000 sec.                            |
| <b>Sensor Resolution<sup>1</sup></b>         | 5MP (2688 x 1944)  | <b>Day/Night</b>            | IR-cut filter for day and night function                  |
| <b>Lens Type</b>                             | Fixed  | <b>IR Cut Filter</b>        | Yes   |
| <b>Focal Length</b>                          | 2.8mm  | <b>IR Range</b>             | 15m / 49ft  |
| <b>Aperture</b>                              | F1.6   | <b>Minimum Illumination</b> | 0.009 lux @ F1.9 (Color)<br>0 lux with IR Illuminators on |
| <b>Iris</b>                                  | Fixed  | <b>Onboard Storage</b>      | Capacity: From 256GB to 2TB<br>Card: MicroSD, SDXC        |
| <b>Field of View (after LDC<sup>2</sup>)</b> | Horizontal: 97° (78°)<br>Vertical: 71° (63°)<br>Diagonal: 128° (91°) | <b>CPU</b>                  | Ambarella CV25S88   |
| <b>Sensor Movement</b>                       | Tilt: 60°<br>Pan: 355°<br>Rotation: 180°                             |                             |   |

#### Standard video settings

|                               |              |                                  |  |
|-------------------------------|--------------|----------------------------------|--|
| <b>Compression</b>            | H.265, H.264 | <b>Historical Video Settings</b> | Adaptive quality <sup>1</sup>  |
| <b>Frame Rate<sup>3</sup></b> | 24fps        | <b>Live Streaming Settings</b>   | High quality (HQ): Up to 3,000 Kbps (default)<br>Standard quality (SQ): Up to 600 Kbps |

#### Standard audio settings

|                       |               |                        |                     |
|-----------------------|---------------|------------------------|---------------------|
| <b>Audio</b>          | Supported     | <b>Interface</b>       | Built-in microphone |
| <b>Audio Capacity</b> | One-way audio | <b>Effective Range</b> | 5m / 15ft           |

#### Power and network

|                                      |  |                     |   |
|--------------------------------------|--|---------------------|---|
| <b>Power Input<sup>4</sup></b>       | With IR: IEEE 802.3af Type 1 PoE<br>Without IR: IEEE 802.3af Type 1 PoE<br>Extended temperature range: N/A   | <b>Connectivity</b> | RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps         |
| <b>Power Consumption<sup>4</sup></b> | With IR: 37-57V, 0.23-0.15A, 8.6W<br>Without IR: 37-57V, 0.11-0.07A, 4.3W<br>Extended temperature range: N/A | <b>RTSP</b>         | RTSP 1.0<br>RFC 2326<br>Max concurrent streams: 2<br>Audio support: Yes |

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -8.5°C / 16.7°F and assumes IR will be enabled.



CD42

Tech Specs



General

|                       |  |                      |   |
|-----------------------|--|----------------------|---|
| Operating Temperature | -10°C to 50°C / 14°F to 122°F  | LED Indicator        | System power and status indicator   |
| Humidity              | 0 to 90%   | Warranty             | 10 Years  |
| Certifications        | FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, UL/cUL/IEC 62368-1, CB, INCM, IK08 impact rating, FY2019 NDAA compliant | Included Accessories | Setup guide, T10 security torx screwdriver, screw pack, mounting template |

Mechanical

|            |  |      |                             |
|------------|--|------|-----------------------------|
| Weight     | Camera: 608g / 21.45oz<br>Mount plate: 140g / 4.94oz   | Body | Aluminum, plastic dome trim |
| Dimensions | Ø: 146.0mm / 5.75in, H: 104.3mm / 4.11in with mount plate<br>Ø: 146.0mm / 5.75in, H: 99.8mm / 3.93in without mount plate |      |                             |

Dimensions



Software capabilities

|                   |  |                       |   |
|-------------------|--|-----------------------|---|
| Alerts            | Camera status, motion detection, people detection, vehicle detection, Person of Interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts | Streaming and Storage | Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP |
| People Analytics  | People search, attribute search, face search, Occupancy Trends, motion search, trajectory analysis, selective face blurring, AI-powered search                                       | Sharing and Privacy   | Live Links, live face blur, privacy regions, audit log  |
| Vehicle Analytics | Vehicle search, attribute search, motion search, trajectory analysis, Occupancy Trends, AI-powered search  |                       |   |



## Ordering Information

### CD42 pricing

| Model Number | MP <sup>1</sup> | WDR | Lens  | IR Range   | Onboard Storage | Maximum SQ Onboard Retention <sup>1</sup> | People/<br>Vehicle Analytics | Cost (MSRP) <sup>USD</sup> |
|--------------|-----------------|-----|-------|------------|-----------------|---|------------------------------|----------------------------|
| CD42-256-HW  | 5MP             | ✓   | Fixed | 15m / 49ft | 256GB           | 30 Days                                   | ✓                            | \$999                      |
| CD42-512-HW  | 5MP             | ✓   | Fixed | 15m / 49ft | 512GB           | 60 Days                                   | ✓                            | \$1,399                    |
| CD42-768-HW  | 5MP             | ✓   | Fixed | 15m / 49ft | 768GB           | 90 Days                                   | ✓                            | \$1,799                    |
| CD42-1TB-HW  | 5MP             | ✓   | Fixed | 15m / 49ft | 1TB             | 120 Days                                  | ✓                            | \$2,199                    |
| CD42-2TB-HW  | 5MP             | ✓   | Fixed | 15m / 49ft | 2TB             | 365 Days                                  | ✓                            | \$3,499                    |

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



## Ordering Information

### Video Security Cloud License pricing (New/Capacity Increase)

| Model Number    | Description                               | Cost (MSRP) USD |
|-----------------|---|-----------------|
| LIC-CAM-1Y-CAP  | 1-Year Camera License, Capacity Increase  | \$199           |
| LIC-CAM-3Y-CAP  | 3-Year Camera License, Capacity Increase  | \$549           |
| LIC-CAM-5Y-CAP  | 5-Year Camera License, Capacity Increase  | \$899           |
| LIC-CAM-10Y-CAP | 10-Year Camera License, Capacity Increase | \$1,799         |

### Video Security Cloud License pricing (Renewal)

| Model Number    | Description                     | Cost (MSRP) USD |
|-----------------|---------------------------------|-----------------|
| LIC-CAM-1Y-RNW  | 1-Year Camera License, Renewal  | \$199           |
| LIC-CAM-3Y-RNW  | 3-Year Camera License, Renewal  | \$549           |
| LIC-CAM-5Y-RNW  | 5-Year Camera License, Renewal  | \$899           |
| LIC-CAM-10Y-RNW | 10-Year Camera License, Renewal | \$1,799         |



## Ordering Information

### Accessories pricing

| Model Number     | Description                              | Cost (MSRP) USD |
|------------------|--|-----------------|
| ACC-CAM-SHIELD-1 | Camera Weather Shield                    | \$79            |
| ACC-MNT-ANGLE-1  | Angle Mount                              | \$149           |
| ACC-MNT-ARM-1    | Arm Mount                                | \$99            |
| ACC-MNT-CJBOX-1  | Circle Junction Box                      | \$109           |
| ACC-MNT-CLIP-1   | Tile Clip Mount                          | \$99            |
| ACC-MNT-CORNER-1 | Corner Mount                             | \$199           |
| ACC-MNT-LBRAC-1  | L-Bracket Mount                          | \$129           |
| ACC-MNT-PEND-1   | Standard Pendant Cap                     | \$69            |
| ACC-MNT-POLE-1   | Pole Mount                               | \$209           |
| ACC-MNT-REC-2    | Recess Ceiling Mount                     | \$149           |
| INJ-POE-PLUS     | PoE Plus (802.3at Type 2) Injector, GigE | \$129           |



## Ordering Information

### Viewing Station pricing

| Model Number | Description          | Cost (MSRP) USD |
|--------------|----------------------|-----------------|
| VX52-HW      | VX52 Viewing Station | \$499           |

### Viewing Station License pricing (New/Capacity Increase)

| Model Number   | Description  | Cost (MSRP) USD |
|----------------|--|-----------------|
| LIC-VX-1Y-CAP  | 1-Year Viewing Station License, Capacity Increase  | \$499           |
| LIC-VX-3Y-CAP  | 3-Year Viewing Station License, Capacity Increase  | \$1,299         |
| LIC-VX-5Y-CAP  | 5-Year Viewing Station License, Capacity Increase  | \$1,999         |
| LIC-VX-10Y-CAP | 10-Year Viewing Station License, Capacity Increase | \$3,999         |

### Viewing Station License pricing (Renewal)

| Model Number   | Description                              | Cost (MSRP) USD |
|----------------|--|-----------------|
| LIC-VX-1Y-RNW  | 1-Year Viewing Station License, Renewal  | \$499           |
| LIC-VX-3Y-RNW  | 3-Year Viewing Station License, Renewal  | \$1,299         |
| LIC-VX-5Y-RNW  | 5-Year Viewing Station License, Renewal  | \$1,999         |
| LIC-VX-10Y-RNW | 10-Year Viewing Station License, Renewal | \$3,999         |