

CD52 Indoor Dome Camera

Reliable 5MP Coverage for Detailed Visibility in Indoor Spaces



Overview

The CD52 dome camera provides precise 5MP coverage in a variety of indoor environments. With a 1 / 2.8" progressive CMOS image sensor, varifocal lens with 2.86x optical zoom, and 30 meters / 98 feet of IR range, the CD52 ensures clear and consistent image quality in a variety of lighting conditions. The CD52 includes an onboard CV25S Ambarella processor to support advanced, privacy-sensitive analytics like AI-powered search, [Occupancy Trends](#), line crossing, loitering, and Person of Interest (POI) alerts. The CD52 excels at covering large indoor spaces like hallways and warehouses where high walls and ceilings make capturing the desired scene otherwise challenging. The camera's optical zoom capabilities ensure that picture quality is maintained when viewing areas of interest from further distances.

The CD52's sleek design and IK08 impact rating enable organizations to deploy a durable, tamper-resistant camera while also keeping aesthetics top-of-mind. Installation is simple and intuitive, and setup is easy to track with an LED status indicator. The included mount plate additionally allows the camera to be mounted to a wall or ceiling without any additional hardware.

Key features

Excellent image quality

- 1 / 2.8" progressive CMOS image sensor
- 5MP resolution
- Varifocal lens with 2.86x optical zoom
- 30 meters / 98 feet of IR range for extensive nighttime visibility

Advanced analytics

- Onboard CV25S Ambarella processor enables people and vehicle analytics
- AI-powered search and AI-powered alerts
- Occupancy Trends for operational insights

Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 365 days (256GB - 2TB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Easy installation

- Mounting plate and screw pack included
- LED light status indicator
- Digital mute switch to quickly enable or disable audio



CD52

Tech Specs

Camera features

Image Sensor	1 / 2.8" Progressive CMOS	Shutter Speed	1 / 30 sec. to 1 / 10,000 sec.
Sensor Resolution¹	5MP (2688 x 1944)	Day/Night	IR-cut filter for day and night function
Lens Type	Varifocal; motorized zoom	IR Cut Filter	Yes
Focal Length	2.8-8mm	IR Range	30m / 98ft
Aperture	F1.3 - F2.4	Minimum Illumination	0.009 lux @ F1.9 (Color) 0 lux with IR Illuminators on
Iris	P-Iris	Onboard Storage	Capacity: From 256GB to 2TB Card: MicroSD, SDXC
Field of View (after LDC²)	Horizontal: 105° - 38° (84° - 37°) Vertical: 77° - 29° (68° - 28°) Diagonal: 126° - 48° (97° - 45°)	CPU	Ambarella CV25S88
Sensor Movement	Tilt: 60° Pan: 355° Rotation: 350°		

Standard video settings

Compression	H.265, H.264	Historical Video Settings	Adaptive quality ¹
Frame Rate³	24fps	Live Streaming Settings	High quality (HQ): Up to 3,000 Kbps (default) Standard quality (SQ): Up to 600 Kbps

Standard audio settings

Audio	Supported	Interface	Built-in microphone
Audio Capacity	One-way audio	Effective Range	5m / 15ft

Power and network

Power Input⁴	With IR: IEEE 802.3af Type 1 PoE Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: N/A	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps
Power Consumption⁴	With IR: 37-57V, 0.30-0.20A, 11.0W Without IR: 37-57V, 0.13-0.08A, 4.7W Extended temperature range: N/A	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio support: Yes

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -8.5°C / 16.7°F and assumes IR will be enabled.



CD52
Tech Specs



General

Operating Temperature	-10°C to 50°C / 14°F to 122°F	LED Indicator	System power and status indicator
Humidity	0 to 90%	Warranty	10 Years
Certifications	FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, CB, NCA, UL/cUL/IEC 62368-1, IK08 impact rating, FY2019 NDAA compliant	Included Accessories	Setup guide, T10 security torx screwdriver, screw pack, mounting template

Mechanical

Weight	Camera: 776g / 29.88oz Mount plate: 140g / 4.94oz	Body	Aluminum, plastic dome trim
Dimensions	Ø: 146.0mm / 5.75in, H: 104.3mm / 4.11in with mount plate Ø: 146.0mm / 5.75in, H: 99.8mm / 3.93in without mount plate		

Dimensions



Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, Person of Interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	Streaming and Storage	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People Analytics	People search, attribute search, face search, Occupancy Trends, motion search, trajectory analysis, selective face blurring, AI-powered search	Sharing and Privacy	Live Links, live face blur, privacy regions, audit log
Vehicle Analytics	Vehicle search, attribute search, motion search, trajectory analysis, Occupancy Trends, AI-powered search		



Ordering Information

CD52 pricing

Model Number	MP ¹	WDR	Lens	IR Range	Onboard Storage	Maximum SQ Onboard Retention ¹	People/ Vehicle Analytics	Cost (MSRP) ^{USD}
CD52-256-HW	5MP	✓	Zoom	30m / 98ft	256GB	30 Days	✓	\$1,199
CD52-512-HW	5MP	✓	Zoom	30m / 98ft	512GB	60 Days	✓	\$1,599
CD52-768-HW	5MP	✓	Zoom	30m / 98ft	768GB	90 Days	✓	\$1,999
CD52-1TB-HW	5MP	✓	Zoom	30m / 98ft	1TB	120 Days	✓	\$2,399
CD52-2TB-HW	5MP	✓	Zoom	30m / 98ft	2TB	365 Days	✓	\$3,699

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



Ordering Information

Video Security Cloud License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-CAM-1Y-CAP	1-Year Camera License, Capacity Increase	\$199
LIC-CAM-3Y-CAP	3-Year Camera License, Capacity Increase	\$549
LIC-CAM-5Y-CAP	5-Year Camera License, Capacity Increase	\$899
LIC-CAM-10Y-CAP	10-Year Camera License, Capacity Increase	\$1,799

Video Security Cloud License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-CAM-1Y-RNW	1-Year Camera License, Renewal	\$199
LIC-CAM-3Y-RNW	3-Year Camera License, Renewal	\$549
LIC-CAM-5Y-RNW	5-Year Camera License, Renewal	\$899
LIC-CAM-10Y-RNW	10-Year Camera License, Renewal	\$1,799



Ordering Information

Accessories pricing

Model Number	Description	Cost (MSRP) USD
ACC-CAM-SHIELD-1	Camera Weather Shield	\$79
ACC-MNT-ANGLE-1	Angle Mount	\$149
ACC-MNT-ARM-1	Arm Mount	\$99
ACC-MNT-CJBOX-1	Circle Junction Box	\$109
ACC-MNT-CLIP-1	Tile Clip Mount	\$99
ACC-MNT-CORNER-1	Corner Mount	\$199
ACC-MNT-LBRAC-1	L-Bracket Mount	\$129
ACC-MNT-PEND-1	Standard Pendant Cap	\$69
ACC-MNT-POLE-1	Pole Mount	\$209
ACC-MNT-REC-2	Recess Ceiling Mount	\$149
INJ-POE-PLUS	PoE Plus (802.3at Type 2) Injector, GigE	\$129



Ordering Information

Viewing Station pricing

Model Number	Description	Cost (MSRP) USD
VX52-HW	VX52 Viewing Station	\$499

Viewing Station License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-CAP	1-Year Viewing Station License, Capacity Increase	\$499
LIC-VX-3Y-CAP	3-Year Viewing Station License, Capacity Increase	\$1,299
LIC-VX-5Y-CAP	5-Year Viewing Station License, Capacity Increase	\$1,999
LIC-VX-10Y-CAP	10-Year Viewing Station License, Capacity Increase	\$3,999

Viewing Station License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-RNW	1-Year Viewing Station License, Renewal	\$499
LIC-VX-3Y-RNW	3-Year Viewing Station License, Renewal	\$1,299
LIC-VX-5Y-RNW	5-Year Viewing Station License, Renewal	\$1,999
LIC-VX-10Y-RNW	10-Year Viewing Station License, Renewal	\$3,999