

## CD32-E Outdoor Dome Camera

# Advanced 3MP Coverage for Monitoring Outdoor Environments



## Overview

The CD32-E outdoor dome camera features a 1 / 2.8" progressive CMOS image sensor and 15 meters / 49 feet of IR range to provide supplemental 3MP coverage in a variety of lighting conditions. The CD32-E includes an onboard CV25S Ambarella processor for advanced analytics like AI-powered search, [Occupancy Trends](#), line crossing, loitering, and Person of Interest (POI) alerts. The CD32-E excels in exterior areas with moderate foot and vehicle traffic where advanced analytics and alerts deliver valuable insights into specific events.

Certified with IP67 weather and IK10 impact ratings, the CD32-E can withstand extreme temperatures and excessive precipitation without compromising aesthetics. Installation and setup are easy to track using the LED status indicator, while the included mount plate makes the device straightforward to install on exterior walls or flat overhangs.

## Key features

### Clear image quality

- 1 / 2.8" progressive CMOS image sensor
- 3MP resolution
- 15 meters / 49 feet of IR range for well-defined nighttime viewing

### Durability and weather protection

- IP67 weather rating
- IK10 impact rating
- Operability between -40°C to 50°C / -40°F to 122°F

### Easy installation

- Mounting plate and screw pack included
- LED light status indicator
- Digital mute switch to quickly enable or disable audio

### Hybrid cloud architecture

- Onboard storage and processing for reduced bandwidth consumption and coverage at scale
- 30 - 90 days (256GB - 768GB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

### Advanced analytics

- Onboard CV25S Ambarella processor enables people and vehicle analytics
- AI-powered search and AI-powered alerts
- Occupancy Trends for operational insights



## CD32-E

### Tech Specs

#### Camera features

<b>Image Sensor</b>	1 / 2.8" Progressive CMOS	<b>Shutter Speed</b>	1 / 30 sec. to 1 / 10,000 sec.
<b>Sensor Resolution<sup>1</sup></b>	3MP (2048 x 1536)	<b>Day/Night</b>	IR-cut filter for day and night function
<b>Lens Type</b>	Fixed	<b>IR Cut Filter</b>	Yes
<b>Focal Length</b>	2.8mm	<b>IR Range</b>	15m / 49ft
<b>Aperture</b>	F1.6	<b>Minimum Illumination</b>	0.009 lux @ F1.9 (Color) 0 lux with IR Illuminators on
<b>Iris</b>	Fixed	<b>Onboard Storage</b>	Capacity: From 256GB to 768GB Card: MicroSD, SDXC
<b>Field of View (after LDC<sup>2</sup>)</b>	Horizontal: 97° (78°) Vertical: 71° (63°) Diagonal: 128° (91°)	<b>CPU</b>	Ambarella CV25S88
<b>Sensor Movement</b>	Tilt: 60° Pan: 355° Rotation: 180°		

#### Standard video settings

<b>Compression</b>	H.265, H.264	<b>Historical Video Settings</b>	Adaptive quality <sup>1</sup>
<b>Frame Rate<sup>3</sup></b>	24fps	<b>Live Streaming Settings</b>	High quality (HQ): Up to 3,000 Kbps (default) Standard quality (SQ): Up to 600 Kbps

#### Standard audio settings

<b>Audio</b>	Supported	<b>Interface</b>	Built-in microphone
<b>Audio Capacity</b>	One-way audio	<b>Effective Range</b>	5m / 15ft

#### Power and network

<b>Power Input<sup>4</sup></b>	With IR: IEEE 802.3af Type 1 PoE Without IR: IEEE 802.3af Type 1 PoE Extended temperature range: IEEE 802.3at Type 2 PoE+	<b>Connectivity</b>	RJ-45 cable connector for network/PoE connection; 10 / 100 Mbps
<b>Power Consumption<sup>4</sup></b>	With IR: 37-57V, 0.23-0.15A, 8.6W Without IR: 37-57V, 0.11-0.07A, 4.3W Extended temperature range: 37-57V, 0.46-0.30A, 16.9W	<b>RTSP</b>	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio support: Yes

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Lens Distortion Correction (LDC) crops the sensor field of view to deliver a rectified, undistorted output image.

3. Frame rate can be adjusted by support.

4. Extended temperature range includes operating temperatures below -8.5°C / 16.7°F and assumes IR will be enabled.



# CD32-E

## Tech Specs



### General

Operating Temperature	-40°C to 50°C / -40°F to 122°F	LED Indicator	System power and status indicator
Humidity	0 to 90%	Warranty	10 Years
Certifications	FCC, ICES, CE, UKCA, RCM, VCCI, KCC, BIS, NOM, UL/cUL/IEC 62368-1, CB, IP67 weather rating, IK10 impact rating, FY2019 NDAA compliant	Included Accessories	Setup guide, wall mount screws and anchors (4x), T10 security torx screwdriver, mounting template, cable gland wrench, desiccant pack, conduit adapter

### Mechanical

Weight	Camera: 847g / 29.88oz Mount plate: 174g / 6.14oz	Body	Aluminum, plastic dome trim
Dimensions	Ø: 155.0mm / 6.10in, H: 114.6mm / 4.51in with mount plate Ø: 155.0mm / 6.10in, H: 107.6mm / 4.24in without mount plate		

### Dimensions



### Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, Person of Interest detection, crowd detection, line-crossing detection, loitering detection, AI-powered alerts	Streaming and Storage	Cloud backup, configurable retention days, selectable storage location, low bandwidth mode, timelapse, RTSP
People Analytics	People search, attribute search, face search, Occupancy Trends, motion search, trajectory analysis, selective face blurring, AI-powered search	Sharing and Privacy	Live Links, live face blur, privacy regions, audit log
Vehicle Analytics	Vehicle search, attribute search, motion search, trajectory analysis, Occupancy Trends, AI-powered search		



## Ordering Information

### CD32-E pricing

Model Number	MP <sup>1</sup>	WDR	Lens	IR Range	Onboard Storage	Maximum SQ Onboard Retention <sup>1</sup>	People/ Vehicle Analytics	Cost (MSRP) <sup>USD</sup>
CD32-256E-HW	3MP	✓	Fixed	15m / 49ft	256GB	30 Days	✓	\$999
CD32-512E-HW	3MP	✓	Fixed	15m / 49ft	512GB	60 Days	✓	\$1,399
CD32-768E-HW	3MP	✓	Fixed	15m / 49ft	768GB	90 Days	✓	\$1,799

1. All our cameras record in "adaptive quality," capturing both standard and high quality streams. Standard quality (SQ) video is stored up to the amount of retention specified by the customer. The amount of high quality video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website: <https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>



## Ordering Information

### Video Security Cloud License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-CAM-1Y-CAP	1-Year Camera License, Capacity Increase	\$199
LIC-CAM-3Y-CAP	3-Year Camera License, Capacity Increase	\$549
LIC-CAM-5Y-CAP	5-Year Camera License, Capacity Increase	\$899
LIC-CAM-10Y-CAP	10-Year Camera License, Capacity Increase	\$1,799

### Video Security Cloud License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-CAM-1Y-RNW	1-Year Camera License, Renewal	\$199
LIC-CAM-3Y-RNW	3-Year Camera License, Renewal	\$549
LIC-CAM-5Y-RNW	5-Year Camera License, Renewal	\$899
LIC-CAM-10Y-RNW	10-Year Camera License, Renewal	\$1,799



## Ordering Information

### Accessories pricing

Model Number	Description	Cost (MSRP) USD
ACC-CAM-SHIELD-1	Camera Weather Shield	\$79
ACC-MNT-ANGLE-1	Angle Mount	\$149
ACC-MNT-ARM-1	Arm Mount	\$99
ACC-MNT-CJBOX-1	Circle Junction Box	\$109
ACC-MNT-CLIP-1	Tile Clip Mount	\$99
ACC-MNT-CORNER-1	Corner Mount	\$199
ACC-MNT-LBRAC-1	L-Bracket Mount	\$129
ACC-MNT-PEND-1	Standard Pendant Cap	\$69
ACC-MNT-POLE-1	Pole Mount	\$209
ACC-MNT-UPEND-1	Umbrella Pendant Cap	\$79
INJ-POE-PLUS	PoE Plus (802.3at Type 2) Injector, GigE	\$129



## Ordering Information

### Viewing Station pricing

Model Number	Description	Cost (MSRP) USD
VX52-HW	VX52 Viewing Station	\$499

### Viewing Station License pricing (New/Capacity Increase)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-CAP	1-Year Viewing Station License, Capacity Increase	\$499
LIC-VX-3Y-CAP	3-Year Viewing Station License, Capacity Increase	\$1,299
LIC-VX-5Y-CAP	5-Year Viewing Station License, Capacity Increase	\$1,999
LIC-VX-10Y-CAP	10-Year Viewing Station License, Capacity Increase	\$3,999

### Viewing Station License pricing (Renewal)

Model Number	Description	Cost (MSRP) USD
LIC-VX-1Y-RNW	1-Year Viewing Station License, Renewal	\$499
LIC-VX-3Y-RNW	3-Year Viewing Station License, Renewal	\$1,299
LIC-VX-5Y-RNW	5-Year Viewing Station License, Renewal	\$1,999
LIC-VX-10Y-RNW	10-Year Viewing Station License, Renewal	\$3,999